

Casio Mobile Technology

Product USPs

IT-9000

1 » Open Architecture

OS: Windows Embedded Mobile 6.5 CPU: PXA320 624 MHz Memory: RAM 256MB F-ROM 256MB

2 » High Resolution Display

- VGA (480 x 640 dots) size
- · 3.7 inch (94mm) transflective colour Blanview LCD
- Suitable for indoor and outdoor use
- Wide viewing angle and low power consumption

3 » Integrated 2MP Digital Camera

- 2.0 mega pixel camera with auto focus
- LED flash
- · Add GPS fix data to JPEG file data

4 » Integrated WLAN and WWAN

- High speed data communication (802.11b/g: up to 54Mbps)
- Wireless standby mode
- WPA and WPA2 security
- Easy to configure with Casio tools
- Quad band, GSM, GPRS (class 12), EDGE (class 12), UMTS, HSDPA (3.5G)

5 » Integrated GPS

- GPS 16 channel receiver
- S-GPS and A-GPS (Assisted GPS)

6 » Barcode Scanning

• CMOS imager for 1D and 2D codes

7 » Rugged Construction

- Drop durability: 1.5M onto concrete
- Dust and splash resistance: IP54
- Operating temperature: -20 to 50°C
- Durable plastic touch panel

8 » Portability

- Ergonomic design, all-in-one device
- Size 255(D) x 79/112(W) x 37/66(H)mm
- Weight: 620-745g

9 » Integrated High Speed Printer

- Drop-In type thermal paper
- 80mm or 58mm paper width
- Printing speed of 28 lines per second
- Roll and label paper
- Graphics and barcode printing

10 » RF-ID and Near Field Communication

- ISO 14443 Type A/B compatible
- ISO 15693 compatible
- · Read-Write capability
- Ideal for secure login/identification and asset tracking

Available Models

IT-9000-05E IT-9000-E IT-9000-G05E IT-9000-GE IT-9000-

IT-9000-25E IT-9000-20E IT-9000-G25E IT-9000-G20E IT-9000-GC25E GMC25E