Getac

Rugged Mobile Computing Solutions

RX10H

Fully Rugged Tablet for Healthcare

- Intel® Core™ M vPro™ Processor
- Premium Thin and Light design weighs 1.2kg and 18.8mm thin
- 10.1'' Full HD LumiBond® 2.0 display with Getac sunlight readable technology and capacitive touchscreen
- Getac's proprietary SnapBack add-on featuring kickstand and hand strap, Smart Card reader or detachable keyboard
- Antimicrobial surface, easily sanitized and certifies to Regulations EN/IEC 60601-1

CERTIFIED MIL-STD 810G | INGRESS PROTECTION IP65 | 4' Drop | CERTIFIED ANSI

Office Dock



Snapback Add-on

RX10H Fully Rugged Tablet for Healthcare

Getac recommends Windows.

Specifications

Operating System	Windows 10 Professional Windows 7 Professional
Mobile Computing Platform	Intel® Core™ M-5Y10c Processor 0.8 GHz Max. 2.0GHz with Intel® Turbo Boost Technology - 4MB Intel® Smart Cache Intel® Core™ M-5Y71 vPro™ Processor 1.2 GHz Max. 2.9GHz with Intel® Turbo Boost Technology - 4MB Intel® Smart Cache
VGA Controller	Intel® HD Graphics 5300
Display	10.1" IPS TFT LCD FHD (1920 x 1200) 800 nits LumiBond® display with Getac sunlight readable technology Capacitive multi-touch screen
Storage & Memory	4GB LPDDR3 expandable to 8GB OPAL 2.0 SSD 128GB / 256GB / 512GB
Keyboard	6 tablet buttons (Windows, Power, Function Key 1, Function Key 2, Barcode Reader Trigger, Volume Up, Volume Down)
Pointing Device	Touchscreen - Capacitive multi-touch screen - Optional dual mode touchscreen (multi-touch and digitizer)
Expansion Slot	Optional 1D/2D imager barcode reader
I/O Interface	HD webcam x 1 8M pixels auto focus rear camera x 1 Headphone out / mic-in combo x 1 DC in Jack x 1 USB 3.0 (9-pin) x 1 USB 2.0 (4-pin) x 1 Docking connector (16-pin) x 1 Micro HDMI x 1 Optional RF antenna pass-through for GPS, WLAN and WWAN
Communication Interface	Intel® Dual Band Wireless-AC 7265, 802.11ac Bluetooth (v4.0)[i] Optional dedicated GPS Optional 4G LTE mobile broadband
Software	Getac Utility Getac Camera Adobe® Reader® Getac Barcode Manager Optional Absolute DDS® Persistence
Security Feature	TPM 2.0 Optional Intel® vPro™ Technology Optional fingerprint scanner or RFID reader[ii, iii] Optional SnapBack add-on : Hand Strap & Kick Stand & Smart Card Reader Optional SnapBack add-on : Hand Strap & Kick Stand & Smart Card Reader & Detachable Keyboard
Power	AC adapter (65W, 100-240VAC, 50 / 60Hz) Li-Ion battery (15.2V, 2160mAh)[iv] LifeSupport™ battery swappable technology Optional High Capacity Battery with Smart Card reader Expansion (14.4V, 5800mAh)[iv]
Dimension (W x D x H) & Weight	280 x 245 x 18.8 mm (11" x 9.65" x 0.74") 1.2kg (2.65 lbs)[v]
Rugged Feature	MIL-STD-810G certified and IP65 certified 4 feet drop resistant Vibration & drop resistant e-Mark certified for vehicle usage Optional ANSI/ISA 12.12.01 Optional EN/IEC 60601-1[vi]
Environmental Specification	Temperature[vii]: - Operating: -21°C to 55°C / -5.8F to 131°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH , non-condensing
Optional Accessories	Carry bag Main battery (15.2V, 2160mAh) High Capacity battery (14.4V, 5800mAh) Multi-Bay Charger (Dual Bay) Multi-Bay Charger (Eight Bay) AC adapter (65W, 100-240VAC) Vehicle adapter (90W, 11-16V DC and 22-32V DC) Capacitive stylus Digitizer Pen Shoulder strap (2-point) Hand Strap & Kick Stand Hand Strap & Kick Stand & Smart Card Reader Hand Strap & Kick Stand & Smart Card Reader & Detachable Keyboard Kick Stand Vehicle dock Office dock Protection film

Docking Solutions

	Serial Port	*External VGA*	*DC in Jack*	*USB*	*LAN*	*HDMI*	*RF antenna connector*
Vehicle Dock	1	--	1	2	1	--	3 (optional)
Office Dock	--	1	1	4	1	1	--

i Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
ii RFID and Fingerprint scanner are mutually exclusive options.
iii 13.56MHz Contactless RFID / NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
iv Battery life testing conducted under MobileMark 2007. Battery performance will vary upon software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. The battery has a limited number of charge cycles and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings.
v Weight and dimensions vary from configurations and optional accessories.
vi Medical Power Supply AC Adapter (EN/IEC 60601-1 certified) sold separately.
vii Tested by a national independent third party test lab following MIL-STD-810G.

Getac

Getac Technology Corporation

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist.,
Taipei City, 11568, Taiwan, R.O.C.
Tel: +886 2 2785 7888
globalmarketing@getac.com
www.getac.com

Copyright © 2017 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Specifications subject to change without notice. V02M06Y17WW

Contact:

RUGGED MOBILE SYSTEMS
TOUGH TECHNOLOGY FOR TOUGH ENVIRONMENTS

RUGGED MOBILE
Systems Ltd
Park View Business
Centre
t: 0845 6520816
e:
Sales@rm-systems.co.uk