

# SK-79

## Ultra-Compact Keyboard with HulaPoint II™

The SK-79 has been designed for those mobile applications when a small-footprint keyboard will come in handy. Featuring an integrated HulaPoint II™ pointing device with dual left-click capability, the SK-79 offers a large amount of functionality in an ultra-small package. Like other keyboards in the iKey line, the SK-79 features sealed industrial silicone rubber keypads, along with robust ABS polycarbonate cases. The SK-79 is less than an inch tall.



## Technical Specifications

### Certifications

NEMA 4X, CE  
UL60950, FCC Part 15 Class B

### Key Switch

MATERIAL: Industrial silicone rubber  
LIFE: Greater than 10 million cycles  
TRAVEL: 0.055 in.  
ACTUATION FORCE: 135g (+/- 30g)  
FEEDBACK: Tactile with mechanical snap

### Power

PS/2: KEYBOARD: 50mA@5V (from Keyboard port)  
POINTER: 35mA@5V (from Mouse port)  
USB: 85mA@5V (from CPU port)

### Temperature Range

STORAGE: -40C to +70C  
OPERATING: -20C to +60C

### Humidity

100%

### Shock

3x11 ms pulses of 50g on each of 3 axes

### Vibration

POWER SPECTRAL DENSITY: 0.04g/Hz  
FREQUENCY RANGE: 20Hz - 2 kHz  
DURATION OF TEST PER AXIS: 3 hours

### Flammability

PRINTED CIRCUIT BOARD: 94 VO  
SILICONE OVERLAY: 94 HB  
INTERFACE CABLE: 94 VO

### Weight

1 lbs (0.45 kg)

### Dimensions

9.27" x 3.87" x 1.00" (w-h-d)  
235.5mm x 98.3mm x 22.9mm

### Cable

LENGTH: 3 feet (0.91 meters)  
DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections), or Single-Cable USB

### Compatibility

PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems  
USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS

### Warranty

1 year limited warranty

### Model Numbers

SK-79-PS2: With PS/2 cable  
SK-79-USB: With USB cable

## Features and Benefits

- Integrated HulaPoint II™ Pointing Device
- Small-Footprint Design
- 12 Function Keys
- 9.27" x 3.87" x 1.00" (w-h-d)
- Meets NEMA 4X (IP65) Specifications
- USB and PS/2 configurations available