



SL-86-911-TP

Mountable Keyboard with Touchpad

The SL-86-911-TP keyboard is designed for vehicle mount in emergency, police, service, transport trucks and marine vessels. Features include a user-friendly integrated touchpad, backlit keys for low-light environments, a one-touch emergency key and mounting holes. The new, easy-to-use integrated touchpad was created to meet public demand for a user-friendly alternative to the traditional HulaPointTM device.



Technical Specifications

Certifications

NEMA 4X, CE UL60950, FCC Part 15 Class B

Key Switch

MATERIAL: Industrial Silicone rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055" (1.4mm) ACTUATION FORCE: 200g (+/-20g) FEEDBACK: Tactile with mechanical snap

Power

PS/2: KEYBOARD: 200mA@5V (from Keyboard TOUCHPAD: 10mA@5V (from Mouse port) USB: 210mA@5V (from CPU port)

Temperature Range

Storage -40C to +65C Operating 0C to +60C

Humidity

100% Humidity Resistant

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2kHz **DURATION OF TEST PER AXIS: 3 hours**

Weight

2.25 lbs (1.02 kg)

Dimensions

11.39" x 7.30" x 1.87" (w-h-d) 289.56mm x 185.42mm x 47.24mm

Cable

LENGTH: 4 ft coiled (1.2m) DESIGN: "Y" PS/2 (providing separate keyboard and mouse connections), or Single-Cable USB

Compatability

PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems USB KEYBOARD/TOUCHPAD: All Windows and Macintosh OS

Warranty

1 Year Limited Warranty

Model Numbers

SL-86-911-TP-PS2: With PS/2 cable SL-86-911-TP-USB: With USB cable

Features and Benefits

- Red Backlit Keys
- 86-Key Functionality
- Fn Key for Secondary Legend Flexibility One-Touch Emergency Key
- Integrated Touchpad
- Meets NEMA 4X (IP65) Specifications
- Mobile Mounting Holes
- 11.39" x 7.30" x 1.87" (w-h-d)