



JLT VERSO+ 10 for Tight Areas

Slim Computer in **Industry's Most Compact Form Factor**, Perfect for Installation in Tight Areas

The VERSO+ 10 computer represents a new class of rugged vehicle terminals. With leading performance in the industry's smallest rugged form factor, it is a perfect choice for installations in tight spaces. Thanks to the JLT QuickLock feature, the computer can easily be mounted and dismounted in a vehicle to simplify service, be moved between vehicles, or be removed at the end of the working day to prevent theft. The scratch resistant touch screen with JLT PowerTouch™ display technology provides the best durability and user experience, while its flush front is simple to keep clean.

Leading Performance and Ruggedness for Heavy Duty Industries

With an Intel® Core™ i5 processor, 64-bit operating system, 8GB DDR3 RAM, and a sunlight-viewable XGA display, the VERSO+ 10 computer is ready for the most demanding applications, such as HD video streaming, GEO calculations, and real-time data processing. To ensure reliable wireless communication over long distances in challenging environments, the VERSO+ 10 features built-in highly sensitive PIFA antennas for WiFi and Bluetooth.

Cradle Optimized for the Logistics Market

The VERSO+ 10 rugged computer is also available with a cradle optimized for indoor or in-cab use in logistics, warehousing and transportation. The exceptional computing power and compact form factor of the VERSO+ 10 computer with the new logistics dock makes it the perfect choice for installation in logistics applications forklifts, picking trolleys and small truck cabins.

Key Features

- High-performance processor for demanding applications
- Market's smallest dimensions make it ideal for installation in tight spaces
- Quick-mount feature simplifies installation, service and switching of units between vehicles
- 10.4" sunlight-readable display with scratch resistant touch screen for long durability
- Built-in PIFA WLAN antennas, custom-made for reliable WiFi environments with poor coverage

User Examples

- Forestry and Agriculture
- Logistics and Warehousing
- Mining and Drilling
- Ports

Because it Works!™

VERSO+ 10 Product Specifications

Base Unit

| | |
|------------------|--|
| Processor | Intel® Core™ i5-4300U |
| | Intel® E3845 |
| Memory | 8GB DDR 3 (Core™ i5) |
| | 4GB DDR 3 (E3845) |
| Display | 10.4" XGA LED 800NIT |
| | 10.4" XGA LED 400NIT |
| | Capacitive touch screen with JLT PowerTouch™ technology and hardened glass |

Storage

| | |
|-------------|--|
| SATA | CFAST 16GB, 32GB, 64GB CFAST up to 128GB available on request |
|-------------|--|

RF Options

| | |
|-----------------|--|
| Radio | Dual-band WLAN 802.11 ac, 802.11 a/b/g/n |
| | Bluetooth v4.0 |
| | 4G (LTE) up to 100 Mbps download speed (optional) |
| GPS | A-GPS/GLONASS in dock (optional) |
| Antennas | WLAN dual diversity antennas (PIFA) |
| | External SMA connectors for 4G and GPS |
| | User configurable external or internal WLAN and Bluetooth antennas |

Interfaces

| | |
|-----------------|----------------------------|
| Ports | 4x USB 2.0 |
| | 1x Ethernet 10/100/1000 |
| | 1x RS232 with 12V |
| Speakers | Waterproof stereo speakers |
| | HD Audio |

Power Supply

| | |
|--------------|---|
| Input | 9-36 VDC Unisolated |
| UPS | Internal battery for graceful shut down at unexpected power outages |

Operating Systems

| | |
|----------------|-----------------------------|
| Windows | Windows 10 |
| | Windows Embedded Standard 7 |
| | Windows 7 |

Physical Characteristics

| | |
|------------------------|--|
| Logistics dock | 251 mm (w) x 207 mm (h) x 48 mm (d) including dock |
| | 9.88 inch (w) x 8.15 inch (h) x 1.89 inch (d) including dock |
| Heavy duty dock | 251 mm (w) x 207 mm (h) x 65 mm (d) including dock |
| | 9.88 inch (w) x 8.15 inch (h) x 2.56 inch (d) including dock |
| Weight | 2.7kg, 4.96 LB |
| Installation | QuickLock, flexible mount/dismount |

Environment

| | |
|------------------------|--|
| Operating temp. | -30° C to 55° C |
| Storage temp. | -35° C to 75° C |
| Humidity | 10–95% RH |
| Dust and water | IP65 when docked with Heavy duty dock QL001 |
| Vibration | 5–500 Hz/0,04 m/s ² XYZ – IEC 60068-2-64 Fh |
| Shock | 30g for 11ms XYZ - IEC 60068-2-27 |
| MIL-SPEC | 810G in applicable areas |


Accessories



Ball joint mount



90W AC/DC



JLT:Care Service Level Agreement

JLT Mobile Computers

Head Office: Isbjörnsvägen 3, SE-352 45 Växjö, SWEDEN

Sales Office: Medborgarplatsen 3, Plan 8, SE-118 26 Stockholm, SWEDEN

Phone: +46 470 53 03 00 **Fax:** +46 470 445 29 **Email:** info@jltmobile.com

North America: 8945 South Harl Avenue, Suite 112. Tempe, Arizona 85284, USA

Toll free US: 844-705-4200 **Intl Phone:** +1 480 705 4200 **Fax:** +1 480 397 1214 **Mail:** USsales@jltmobile.com

www.jltmobile.com

