



**ZONE 1/21**

## IS910.1

The IS910.1 is the tablet for use in ATEX zones 1/21. The 8" tablet is highly robust, powerful and offers many technical advantages: 8.400 mAh Battery, Qualcomm Snapdragon 2 GHz, NFC, Android™ 8.0 etc.

› Please visit our website and you will find more detailed information, as well as an overview of compatible accessories. › i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi® is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. › © 2018 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1016MD02REV01\_EN

## TECHNICAL FEATURES



ATEX approval:  
Ex-zone 1/21  
Ⓜ II 2G Ex ib IIC T4 Gb  
Ⓜ II 2D Ex ib IIIC T135°C  
Db IP6X



IECEx approval:  
Ex-zone 1/21  
Ex ib IIC T4 Gb  
Ex ib IIIC T135°C Db IP6X



Approved for North  
America:  
Class I, II, III Division 1  
Groups A B C D E F G, T4  
Intrinsically Safe



Approved for Russia:  
1Ex ib IIC T4 Gb X  
Ex ib IIIC T135°C Db X  
IP64



Android 8.0



GSM:  
850/900/1800/1900MHz  
WCDMA:  
900/1800/2100 or  
850/1900/2100MHz  
LTE-FDD EU: B1/B3/B7/  
B20/B28  
LTE-FDD US: B2/B4/B7/B17  
LTE-TDD: B38/B39/B40/B41  
TD: B34/B39



2,4 GHz: Wifi IEEE 802.11  
b/g/n



Bluetooth® 4.1 LE



size: 235x154x23 mm,  
weight: 880 g



external memory  
microSD up to 32 GB



Qualcomm Snapdragon  
625 (MSM8953), 2 GHz,  
3 GB RAM  
32 GB internal memory  
24 GB accessible



Near Field  
Communication



magnetic charging port



2 cameras:  
8 MP rear camera and  
5 MP front camera



SOS-key

## FURTHER FEATURES



waterproof: 1 hour  
up to 2 m, impervious to  
dust and microparticles



operation range from  
-20 °C to 60 °C



8" RugDisplay-Glass  
multi capacitive touch-  
screen with a resolution  
of 1200 x 1920 pixel



usable with gloves



8.400 mAh battery



GPS, AGPS, Glonass,  
BeiDou



Location, acceleration,  
gravity, linear acceleration,  
gyroscope, ambient light,  
temperatur and humidity,  
magnetic, proximity and  
pressure sensor



Push-To-Talk  
PTT ready (third party  
application provided)



Loneworker protection  
LWP ready (third party  
application provided)

## CONTENTS

Tablet with integrated battery, charger, i.safe PROTECTOR 2.0 USB cable,  
i.safe PROTECTOR 3.0 USB cable, quick start manual and safety instructions