



aegex10™ intrinsically safe tablet

Aegex Technologies provides intrinsically safe solutions for the world's most hazardous industrial operations in oil and gas, chemical, mining, pharmaceutical, public safety, utilities and other industries with explosive environments. Aegex solutions bring real-time connectivity to hazardous areas, helping organizations harness the power of data to optimize efficiency, safety and productivity.



Oil & Gas



Chemical



Mining



Pharmaceutical



Public Safety



Utilities

The **aegex10™ Intrinsically Safe Tablet** is the most advanced, efficient, lightweight and rugged Windows tablet that is purpose-built for **Zone 1 / Division 1 hazardous areas**. Simple to deploy, it is the basis for an Industrial Internet of Things platform for hazardous industries, allowing operations to easily begin their digital transformation to Industry 4.0.

● Purpose-Built Intrinsically Safe and Enterprise-Class Tablets:

Aegex devices are certified ATEX/IECEX Zone 1; certified by SGS to UL 913 Class I, II, III Division 1 Groups A-G; and IP65 for hazardous (classified) locations.

● Solutions for All Hazardous Zones and Jobs:

Aegex devices run the operating system and applications that allows for secure enterprise deployments.

● Enterprise Collaboration

Aegex devices use 4G LTE or Wi-Fi for real-time communications.



Certified ATEX/IECEX Zone 1

Certified by SGS to
UL 913 C I, II, III Div 1

10.1" WUXGA Display

Powered by Intel
Atom Quad Core

Windows 10

Intel Security Suite



aegex.com



SPECIFICATIONS

Intrinsically Safe Certifications

UL913 5th edition:
 C I, II, III Div 1 Gr A-G T4, T_{amb} = -10°C...+50°C
 Cl Z0 Gr IIC T4 IP65, T_{amb} = -10°C...+50°C
 CAN/CSA-22.2 Part 157

IECEX 60079-0 & -11:
 Ex ib IIC T6 Gb, T_{amb} = -10°C...+50°C
 Ex ib IIIC T85°C Db IP6X, T_{amb} = -10°C...+50°C
 Ex ib I Mb, T_{amb} = -10°C...+50°C

ATEX 60079-0 & -11:
 Ⓜ II 2G Ex ib IIC T6 Gb, T_{amb} = -10°C...+50°C
 Ⓜ II 2D Ex ib IIIC T85°C Db IP6X, T_{amb} = -10°C...+50°C
 Ⓜ I M2 Ex ib I Mb, T_{amb} = -10°C...+50°C

Exterior

Dimensions:
 273 x 185 x 16.8 mm (10.75 x 7.28 x 0.66 in)
 Weight: 980 grams (2.16 lbs)
 IP65

Display

Screen: 10.1" AHVA Full HD Plus
 Resolution: 1920 x 1200
 Capacitive touch: Multi-touch
 Contrast 800:1
 Viewing angle (up/down, left/right) 170°

Battery Life

Up to 12 hours of web browsing (Battery: 3.8V, 8700mAh, 33Wh)

Charging time (in standby)

Docking station: 0-90% in 2.5 hours, to 100% in approx. 3.5 hours
 USB charger: 0-90% in 4 hours, to 100% in approx. 5.5 hours

Storage/RAM

128GB storage / 4GB RAM

CPU & Wireless

Intel® Quad-Core Atom processor
 2.39GHz*, 4G LTE available
 Wi-Fi 802.11ac/802.11 a/b/g/n dual band
 (2.4GHz and 5GHz)
 Bluetooth® 4.0 Low Energy technology
 NFC
 Intel Wireless Display

* LTE (EU, US, AU): Telit LN940A9

- LTE: Band 1, 2, 3, 4, 5, 7, 8, 12, 13, 17, 18, 19,
 20, 21, 25, 26, 28, 29, 30, 38, 39, 40, 41, 66
 - WCDMA: Band 1, 2, 3, 4, 5, 6, 8, 19
 - GSM/GPRS/EDGE: N/A

LTE (North America): Sierra EM7355

- LTE: FDD Band 2,4,5,13,17,25
 all bands with diversity
 - UMTS/HSPA+: Band 1,2,4,5,8,
 all bands with diversity
 - CDMA 1xRTT/EV-DO Rev A: BC0, BC1, BC10
 - GSM/GPRS/EDGE: Quad-Band

LTE (international): Huawei ME936

- LTE: FDD Band 1,2,3,4,5,7,8,13,17,20,
 all bands with diversity
 - WCDMA/HSDPA/HSUPA/HSPA+:
 Band 1,2,4,5,8, all bands with diversity
 - GSM/GPRS/EDGE: 850/900/1800/1900MHz

Location

GPS / GLONASS
 (cold start <30s, warm start < 5s)

Ports

Full-size USB 2.0
 USB 3.0, Ethernet, and HDMI on system connector
 Micro USB for charging
 Charging pads (12V)
 microSDXC™ card slot (supports up to 2TB)
 Headset jack

Software

Windows 10 IoT Enterprise

Cameras, Video & Audio

8.0 megapixel autofocus rear-facing camera with flash, full HD video
 2.0 megapixel front-facing camera full HD video
 Front and rear microphones
 Stereo speakers

Sensors

Ambient light sensor, Accelerometer,
 Gyroscope, E-Compass,
 SAR proximity sensor

Security

Silicon Level, Intel Security
 (SMER, PDRNG, fTPM, and TPM 2.0)
 Software Level
 Device Control
 Windows 10 Mobile Device Management
 BitLocker

In the box

aegex10™ intrinsically safe tablet
 Wall charger (power supply + USB cable)



To request a demo or to talk to a product specialist, please contact our nearest office or go to:

www.aegex.com

UNITED STATES

Headquarters (Atlanta)

Phone: +1 (470) 242-4000

Email: contact@aegex.com

UNITED STATES

Sales (Houston)

Phone: +1 (713) 487-5588

Email: contact@aegex.com

EUROPE

Sales (Netherlands)

Phone: +31 10 808 1090

Email: contact@aegex.com

EUROPE

Sales (United Kingdom)

Phone: + 44 2380 302 456

Email: contact@aegex.com

MIDDLE EAST

Sales (UAE)

Phone: +971 4 813 7820

Email: contact@aegex.com

 @aegextech

 contact@aegex.com



© 2019 Aegex Technologies, LLC. All Rights Reserved. The trademarks, logos, and service marks ("Marks") included herein are the property of Aegex Technologies, LLC or of their respective owners. AEGEX, AEGEX TECHNOLOGIES, aegex.com, and the Aegex logo are all trademarks of Aegex Technologies, LLC and/or its affiliates. Use of any Mark is not permitted without the prior written consent of Aegex Technologies, LLC or of the respective owner. The information in this document is subject to change without notice. Aegex and/or its representatives cannot be held responsible for any errors or inaccuracies within this document.

*Base Frequency 1.59 GHz, Burst Frequency 2.39 GHz

*Subject to verification of local carrier requirements

**P2P: ISO 18092, Reader/Writer: ISO 14443 -A-B, MIFARE, FeliCa®, ISO 15693, NFC Forum Tag Types 1 to 4
 Card emulation: ISO 14443 -A-B-B', MIFARE, FeliCa RF, Distance up to 3 cm