



X500 FULLY RUGGED NOTEBOOK

- Intel® Core™ i7-7820HQ Processor
- 15.6" TFT LCD FHD with Getac QuadraClear® Sunlight Readable Display
- Optional NVIDIA® GeForce® GTX950M 4GB discrete graphic controller
- Multimedia Bay & PCI/PCIe 3.0 Expansion Unit



PCI/PCI-Express 3.0 Expansion Unit



Multimedia Bay 2nd Storage



Specifications

Operating System

Windows 10 Pro

Mobile Computing Platform

Intel® Core™ i7-7820HQ 2.9GHz, Max. 3.9GHz
- 8MB Intel® Smart Cache

Intel® Core™ i5-7440HQ 2.8GHz, Max. 3.8GHz
- 6MB Intel® Smart Cache

VGA Controller

Intel® HD Graphics 630
Optional NVIDIA® GeForce® GTX950M 4GB discrete graphic controller

Display

15.6" TFT LCD FHD (1920 x 1080)
1000 nits QuadraClear® sunlight readable display
Optional resistive touch screen

Storage & Memory

8GB DDR4 expandable to 64GB¹
SATA HDD 500GB; Optional SATA HDD 1TB
Optional SATA SSD 512GB / 1TB

Keyboard

LED backlit membrane keyboard with integrated numeric keypad
Optional LED backlit rubber keyboard

Pointing Device

Touchscreen
- Optional pressure sensitive touchscreen
Touchpad
- Glide touchpad with scroll bar

Expansion Slot

Optional PCMCIA Type II x 1
ExpressCard/54 x 1
Smart Card reader x 1
SD Card Reader x 1

Multimedia Bay

DVD super multi drive
Optional 2nd battery: 10.8V, 8700mAh
Optional 2nd storage: HDD 500GB / 1TB ;
SSD 512 GB / 1TB

I/O Interface

Serial port (9-pin; D-sub) x 2
External VGA (15-pin; D-sub) x 1
Microphone (Mini-jack) x 1
Audio output (Mini-jack) x 1
DC in Jack x 1
USB 3.0 x 4
LAN (RJ45) x 2
HDMI x 1
Docking connector x 1
Optional RF antenna pass-through for GPS²,
WLAN and WWAN
Optional FHD webcam x 1

Communication Interface

10/100/1000 base-T Ethernet
Intel® Dual Band Wireless-AC 8265, 802.11ac
Bluetooth® (v4.2)³
Optional dedicated GPS
Optional 3G mobile broadband

Security Feature

Intel® vPro™ Technology
TPM 2.0
Smart Card reader
Kensington lock

Power

AC adapter (150W, 100-240VAC, 50 / 60Hz)
Li-Ion smart battery (10.8V, 8700mAh)
Optional Multimedia Bay 2nd Li-Ion smart battery
(10.8V, 8700mAh)

Dimension (W x D x H) & Weight

410 x 290 x 65mm (16.1 x 11.4 x 2.5)
5.2 kg (11.4 lbs)⁴

Rugged Feature

MIL-STD-810G certified and IP65 certified
MIL-STD-461G certified⁵
Optional ANS/ISA 12.12.01⁶
Full magnesium alloy case
Shock-protected removable HDD
Vibration & drop resistant

Environmental Specification

Temperature⁷:
- Operating: -20°C to 55°C / -4°F to 131°F
- Storage: -40°C to 71°C / -40°F to 160°F
Humidity:
- 95% RH, non-condensing

Software

Getac Utility
Adobe® Reader®
Optional Absolute DDS® Persistence

Accessories

Backpack
Multi-Bay Charger (Dual Bay)
MIL-STD-461 certified AC adapter (150W,
100-240VAC)
Stylus
Protection film
PCI or PCI-Express 3.0 Expansion Unit (x 2 slots)
Main battery (10.8V, 8700mAh)
AC adapter (150W, 100-240VAC)
Multimedia bay 2nd battery (10.8V, 8700mAh)
Multimedia Bay 2nd HDD
Vehicle dock
Office dock

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our new Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

Standard

5 years Bumper-to-Bumper

- i Share memory size may vary by different operating system and RAM size.
- ii Optional RF antenna pass-through for GPS, PCI or PCI-Express Expansion Unit are mutually exclusive options.
- iii Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- iv Weight and dimensions vary from configurations and optional accessories.
- v MIL-STD-461G 150W AC adapter sold separately.
- vi PCI expansion unit or PCI-E option is not available with ANSI / ISA 12.12.01 configurations.
- vii Tested by a national independent third party test lab following MIL-STD-810G.

X500

Fully Rugged Notebook



Docking Solutions

	Vehicle Dock	Office Dock
Serial Port	2	1
External VGA	1	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	USB 2.0 x 4	USB 2.0 x 2 USB 3.0 x 2
LAN	1	1
RF Antenna Connector	3 (optional)	--

Getac

Getac (UK) Ltd.

Getac House, Stafford Park 12,
Telford, Shropshire TF3 3BJ, United Kingdom
Tel : +44 (0) 1952 207 222
Sales-Getac-UK@getac.com | en.getac.com



Copyright © 2018 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference only,
available specification shall be subjected to quotation by request. V01M12Y18WW