



# JLT6012

## 12" vehicle-mount computer

### Maximum productivity for logistics applications

Need a future-proof system that's as user-friendly as it is smart? Meet the JLT6012™ computer. We created an innovative architecture that makes it easy to integrate new technology, giving you the flexibility to adapt to changing needs and keep up-to-date with developments.

Productivity has been the number-one priority in every step of our development of the JLT6012 computer. That takes everything into account; from outstanding user acceptance to the highest reliability. This computer runs both Windows™ and Android™ operating systems and can be installed in virtually any vehicle, electrical or combustion powered, without the need for external adapters. State-of-the-art wireless technology ensures reliable connectivity in less than optimal conditions. The intuitive touchscreen is simple to use, even when wearing gloves. The screen is virtually unbreakable, overcoming the most common failure point for rugged computers. With the JLT6012 onboard, you're ready for the future of logistics – whatever it brings.



#### KEY FEATURES

- Runs both Android and Windows operating system
- 12" capacitive touch with JLT PowerTouch™
- Intel® E3845 processor
- IP65 waterproof and dustproof
- Virtually unbreakable JLT PowerTouch™ display
- Dual-diversity IFA WLAN antennas
- Easily accessible programmable function buttons
- Integrated wide-range 9-60 VDC isolated power supply

#### HIGHLIGHTS



##### Installation in almost any vehicle without adapters

Integrated wide-range 9-60 VDC isolated power supply enables installation in most vehicle types without external adapters



##### Data input made easy

Two keyboard options are available – customizable on-screen versions or external standard keyboards



##### Virtually unbreakable display

JLT PowerTouch™ display technology has outstanding resistance to wear and tear

# JLT6012

## 12" vehicle-mount computer

### BASE UNIT

---

#### Processor

Intel® E3845

#### Memory

4GB On-board

#### Display

12.1" XGA LED 1000 NIT

12.1" XGA LED 500 NIT

Capacitive touch screen with JLT PowerTouch™ technology and hardened glass

Light sensors for adjustable auto-dimming

### STORAGE

---

#### SATA

M.2 32GB, 64GB, 128GB, 256GB

### RF OPTIONS

---

#### Radio

Dualband WLAN 802.11 ac, 802.11 a/b/g/n

Bluetooth v4.2 + BLE

RFID for login

#### Antennas

WLAN dual diversity antennas (IFA)

User configurable external or internal WLAN and Bluetooth antennas

### INTERFACES

---

#### Ports

1x USB 3.0

3x USB 2.0

1x Ethernet 10/100/1000

1x RS232 with customer configurable 5V or 12V

I/O Port

#### Speakers

Encapsulated audio exciters

HD audio

#### Buttons

6x Capacitive touch buttons

Power

LED dimming +/-

3x Configurable

#### LED indicators

Power status

Disc activity and Wi-Fi connection

### SECURITY

---

TPM module

### POWER SUPPLY

---

#### Input

9-60 VDC isolated

#### UPS

Internal battery for graceful shut down at unexpected power outages

#### Power consumption

20 W\* (max 40 W, stand by/off mode 0.4 W)

### OPERATING SYSTEMS

---

#### Windows

Windows 10 IoT LTSC

#### Android

Android 8.1 Oreo

### PHYSICAL CHARACTERISTICS

---

#### Dimensions

292mm (w) x 231mm (h) x 50mm (d)

11.5 inch (w) x 9.1 inch (h) x 2 inch (d)

#### Weight

2.85 kg, 6.45 LB

### ENVIRONMENT

---

#### Operating temperatures

-30° C to 55° C / -22° F to 131° F

#### Storage temperatures

-35° C to 75° C / -31° F to 167° F

#### Humidity

10–95% RH

#### Dust and water

IP65 - IEC 60529:2001

#### Vibration

5–500 Hz/0,04 m/s<sup>2</sup> XYZ - IEC 60068-2-64 Fh

#### Shock

30g for 11ms XYZ - IEC 60068-2-27

#### MIL-SPEC

810G in applicable areas

\*Windows running in idle with full screen brightness (STD bright)