



## 10.1" fully rugged Windows 11 Pro Tablet

# **TOUGHBOOK G2 mk3 Quick Release SSD**

The TOUGHBOOK G2 is the next generation rugged device for mobile workforces. It offers all the benefits of the latest technology, while maintaining important access to legacy systems. All of this, wrapped up in a more flexible, secure and ultimately even more useable device.

#### **Key Features**

Intel® Core™ Ultra5 processor 135U (with Intel vPro® Technology)

#### Windows 11 Pro

10.1" Active Matrix (TFT) colour LCD 1920 x 1200 (WUXGA) LCD with sunlight-viewable glove-enabled capacitive touchscreen (up to 1.000cd/m<sup>2</sup>), IP55 Digitiser

IP65 Water and dust resistant\*\*\*\*, Tested against MIL-STD 810H\*\*\*\*

Quick Release end user replaceable SSD









## TOUGHBOOK G2 mk3 Quick Release SSD

### **EVOLVED TO ADAPT**

An evolution of the best-selling Panasonic Toughbook G1 tablet and 20 detachable, this latest tablet is powered by the 12th Generation Intel®Core™ i5-1245U vPro™ processor, delivering incredible performance, and is shipping with Windows 11 Pro. It also has a rich set of business interfaces with additional customisable options to meet a worker's needs. With its long battery life and outdoor viewing,glove-enabled touchscreen, it's a versatile yet tough technology companion for mobile workers.

https://eu.connect.panasonic.com/g b/en/toughbook/toughbook-g2series/toughbook-g2-mk3-quickrelease-ssd







Model	FZ-G2 mk3 Quick Release SSD, 16/32GB RAM, 512GB/1TB/2TB SSD, battery pack, digitis
	pen
Operating System	Windows 11 Pro
Mobile Computing Platform	Intel® Core™ Ultra5 processor 135U (with Intel vPro® Technology)
Graphic Chip	Intel® Graphics (Built-in CPU)
RAM	16GB (max. 32GB) DDR5x
Storage	Quick Release 512GB OPAL NVMe SSD (up to 2TB optional)
LCD	10.1" Active Matrix (TFT) colour LCD 1920 x 1200 (WUXGA) LCD with sunlight-viewable glove-enabled capacitive touchscreen (up to 1.000cd/m²), IP55 Digitiser
Wireless	Mobile Broadband*: 4G or 5G with SIM/eSIM support Wireless
	LAN: Intel® Wi-Fi6E AX211
	GPS*: U-Blox NEO-M9N Series (not compatible to 5G model)
	LAN: IEEE 802.3 10Base-T / IEEE 802.3u 100BASE-TX / IEEE 802.3ab 1000BASE-T
	Bluetooth™: 5.3 Class 1 Mobile
Interfaces	USB 3.2 Gen 1 Type A: x1
	Thunderbolt 4: x1
	LAN: x1
	Dual Antenna Connector: x1
Rear expansion area	Smart Card Reader, HF-RFID (NFC) Reader, Fingerprint Reader***
Top Expansion Area	Serial, 2D Barcode Reader, 2nd USB 2.0, 2nd LAN, Thermal by FLIR, Micro-SD**
Front Camera	2 MP with IR / privacy shutter (Windows Hello compliant)
Rear Camera	13mpixel with autofocus and LED flash
Sound	Intel® High Definition Audio subsystem support, Stereo speaker
Security	TPM (TCG V2.0 compliant), Integrated hardware security lock slot, Windows Hello compliant Webcam
Keyboard & Input (Keyboard)	x1*
Pointing device: Touchscreen (Touch panel)	Touchpad
Dimensions: Main Unit + Keyboard (WxHxD)	287 mm x 235 mm x 52.7 mm / 11.3" x 9.3" x 2.1" (without protruding parts)
Dimensions: Main Unit (WxHxD)	279 mm x 188 mm x 28.1 mm / 11.0" x 7.4" x1.1" (without protruding parts)
Weight: Main Unit	Approx. 1.32kg / 2.9lb
Battery Life	Approx 15 hours (Mobile Mark™ 25)
Power Supply: AC Adaptor	Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05 A
Power Supply: Battery	Li-ion 10.8V, 6300mAh min. (68Whr)
Power Supply: Hot Swap	Standby function, ACPI BIOS,
	Hot swap optional
Drop resistance	MIL-STD 810H, 180cm ****
	IEC529 (IIS C0920) IP6x ****
Dust resistance	
Water resistance	IEC529 (JIS C0920) IPx5 ****
Water resistance Operating temperature	IEC529 (JIS C0920) IPx5 **** MIL-STD 810H, -29 °C to 63 °C ****
Water resistance Operating temperature	IEC529 (JIS C0920) IPx5 ****
Water resistance Operating temperature	IEC529 (JIS C0920) IPx5 **** MIL-STD 810H, -29 °C to 63 °C **** Power Supply, Power Cord,
Water resistance Operating temperature Included in the box	IEC529 (JIS C0920) IPx5 **** MIL-STD 810H, -29 °C to 63 °C **** Power Supply, Power Cord, Display cleaning cloth and User Manual
Water resistance Operating temperature Included in the box Integrated options	IEC529 (JIS C0920) IPx5 **** MIL-STD 810H, -29 °C to 63 °C **** Power Supply, Power Cord, Display cleaning cloth and User Manual Port Replicator:x1
Dust resistance Water resistance Operating temperature Included in the box Integrated options Footnote Description	IEC529 (JIS C0920) IPx5 **** MIL-STD 810H, -29 °C to 63 °C **** Power Supply, Power Cord, Display cleaning cloth and User Manual Port Replicator:x1 * Optional
Water resistance Operating temperature Included in the box Integrated options	IEC529 (JIS C0920) IPx5 **** MIL-STD 810H, -29 °C to 63 °C **** Power Supply, Power Cord, Display cleaning cloth and User Manual Port Replicator:x1 * Optional ** One option exlusive possible in Top Expansion Bay Area, End User replaceable
Water resistance Operating temperature Included in the box Integrated options	IEC529 (JIS C0920) IPx5 **** MIL-STD 810H, -29 °C to 63 °C **** Power Supply, Power Cord, Display cleaning cloth and User Manual Port Replicator:x1 * Optional
Water resistance Operating temperature Included in the box Integrated options	IEC529 (JIS C0920) IPx5 **** MIL-STD 810H, -29 °C to 63 °C **** Power Supply, Power Cord, Display cleaning cloth and User Manual Port Replicator:x1 * Optional ** One option exlusive possible in Top Expansion Bay Area, End User replaceable

#### TOUGHBOOK G2 mk3 QR SSD : September 2024

Intel, the Intel logo, Intel Core, Intel vPro, Core Inside and vPro Inside are trademarks of Intel Corporation in the U.S. and other countries. Microsoft® and Windows® are registered trademarks of Microsoft® Corporation of the United States and/or other countries. All other brand names shown are the registered trademarks of the relevant companies. All rights reserved. All working conditions, times and figures quoted are optimum or ideal levels and may differ as a result of individual and local circumstances.